



INDEX TO NOTES

- 1 BUILT UP ROOFY SLAQ ON 1 1/2" RIGID INSULATION.
- 2 BUILT UP ROOFY SLAQ ON 1/2" RIGID INSULATION
- 3 MINERAL FLASHING
- 4 GALV. S.M. COUNTER FLASHING
- 5 CONT. GALV. S.M. FLASHING PAINTED
- 6 DEL. 2X6 PLATE CONT.
- 7 DEL. 2X6 PLATE CONT.
- 8 2X6 PLATE CONT.
- 9 1X2 BLOCKING CONT.
- 10 ASPHALT SHINGLES ON 3/8" FELT
- 11 5/8" PLYWOOD SHEATHING
- 12 1/2" PLYWOOD SHEATHING
- 13 1/4" CEMENT ASBESTOS SIDING - FLASH & WATERPROOF ALL JOINTS
- 14 1X4 PURLINS CONT.
- 15 1X10 BLOCKING CONT.
- 16 PREFAB WOOD FRAMES @ 24" O.C. @ 1/4" B.C.A. GALV. HURR. ANCH. @ 24" FRM.
- 17 STUCCO ON GALV. METAL LATH ON 3/8" FELT - SEE ELEVATIONS FOR LOCATION OF THIS EXPANSION JOINTS
- 18 2X4 @ 24" PRES. TRTD PLATE CONT. 1/2" AB @ 2' O.C.
- 19 1 1/2" RIGID INSULATION
- 20 CONT. DRIP
- 21 POURED CONC. SLAB - SEE STRUCT. DRVGS.
- 22 SPRAYED FINISH ON CONC. SLAB - SEE SPECS.
- 23 DRYWALL
- 24 1X2 PRES. TRTD FURRING @ 16" O.C.
- 25 1X2 CONT. BLOCKING OVER WINDOWS & DOORS
- 26 8" CONC. BLOCK, COMMON BOND 1/2" HOR. WALL REIN. EVERY 3RD CRS.
- 27 PRECAST CONC. LINTEL - SEE STRUCT. DRVGS.
- 28 MARBEL STOOL TYPICAL ALL WINDOWS
- 29 POURED CONC. SILL 1/2" AB @ 4' O.C.
- 30 STUCCO
- 31 ALUM. WINDOW - SEE SCHEDULE FOR TYPE & SIZE
- 32 ALUM. SLIDING GLASS DOOR - SEE SCHED FOR SIZE
- 33 WOOD BASE - TYPICAL - SEE SCHEDULE
- 34 COMPACTED FILL - SEE SPECS.
- 35 1/2" EXP. JOINT MATERIAL CONT.
- 36 THICKEN SLAB - SEE STRUCT. DRVGS.
- 37 FOUNDATION WALL BEYOND
- 38 POURED CONC. GRADE BEAM - SEE STRUCT. DRVGS.
- 39 DAMPROOFING - SEE SPECS.
- 40 8" CONC. BLOCK, COMMON BOND 1/2" HOR. WALL REIN. EVERY 3RD CRS.
- 41 ALUM. RAILING - SEE DETAIL
- 42 6" CONC. CUT LINTEL BLK INVERTED 1/4" CONT. FILL BLK 1/2" CONC. CONT.
- 43 #4 DOVELS @ 4' O.C. FILL BLK CELL 1/2" CONC. @ DOVELS.
- 44 1/2" x 1/2" ALUM. SCUFFERS - SEE ELEVATIONS FOR LOC.
- 45 PRECAST CONC. SILL (ALL WINDOWS 1/2" BLK WALLS BELOW)
- 46 90° FELT ISOLATION JOINT TYPICAL
- 47 POURED CONC. S.M. - SEE STRUCT. DRVGS.
- 48 POURED CONC. TERRACE SLAB - SEE PLAN FOR LOCATION
- 49 2X3 PRES. TRTD PLATE CONT. 1/2" AB @ 4' O.C.
- 50 FIBER CANT
- 51 8" CONC. BLOCK, COMMON BOND 1/2" HOR. WALL REIN. EVERY 3RD CRS, TOOL ALL EXPOSED JOINTS
- 52 PRESTRESSED CONC. HOLLOW CORE FLAT SLAB - SEE STRUCT. DRVGS.
- 53 GALV. S.M. EXPANDABLE FLASHING ON 4X4 FT. WOOD CANT
- 54 POURED CONC. ROOFING - SEE STRUCT. DRVGS.
- 55 POURED CONC. FILL - SEE STRUCT. DRVGS. FOR CONN. DETAILS.
- 56 2X4 PRES. TRTD PLATE CONT. 1/2" AB @ 4' O.C.
- 57 GALV. S.M. GRAVEL STOP CONT. - SEE PLAN & ELEV. FOR LOCATION OF SCUFFERS
- 58 STUCCO WASH
- 59 CHAINLINK ROOF CONST. - SEE SPECS.
- 60 1" PVC. OVERFLOW PIPE - SEE SHT. NO. 8 FOR LOCATI.